Product End of Life Instructions

Variable speed drive, Altivar Machine ATV340, 7.5kW, 400V, 3 phases, Ethernet

Altivar Machine ATV340







ENVEOLI1609005_V2 07-2024

⚠

Potential disassembly risks

The information provided in this document assumes that the product is completely deenergized and uninstalled (refer to the instructions provided in the appropriate product manuals).

Dismantling/disassembling the product may entail hazards caused by, for example, sharp edges, chemical aggression or ejected parts.

A WARNING


HAZARD DUE TO INSUFFICIENT PROTECTION

- Implement all safety measures required by the applicable regulations and by the processes used to dismantle/disassemble and dispose of the product.
- Use all necessary personal protective equipment such as gloves and goggles.

Failure to follow these instructions can result in death or serious injury.

ENVEOLI1609005_V2 07-2024

► End of Life Instructions



ENVEOLI1609005_V2 07-2024

ENVEOLI1609005_V2 - End of Life Instructions - Variable speed drive, Altivar Machine ATV340, 7.5kW, 400V, 3 phases, Ethernet

Recommendation	Number on drawing	Component / Material Weight (in g)		Comment
To be depolluted	1	Electronic Board (Power and Communication) > 10cm ²	1084,74	
To be depolluted	2	Cable (high current)	21,34	
To be depolluted	3	Electrolyte capacitors which size: height > 25 mm, diameter > 25 mm or proportionately similar volume	354	
To be dismantled	4	Steel	74,15	Ground Bar - Ground Plate
To be dismantled	5	Aluminium	531,81	Heatsink
To be dismantled	6	PC, ABS-PC, PA, PA6, HDPE, SAN with or without additive, PP+EPDM and PP	710,6	Housing - Support - Cover
Other			223,36	



Product description

Manufacturer identification	Schneider Electric Industries SAS			
Brand name	Schneider Electric			
Product function	The main function of the Altivar Machine product range is the speed control and variation of a 3-phase synchronous, asynchronous or reluctance electric motor for fluid management and industrial applications. ATV340 has been designed to meet the needs of applications for harsh environments, such as vibration, shock and non-conductive dust and where high temperature resistance up to 60 °C is needed.			
Product reference	ATV340U75N4E			
Total representative product mass	3 kg			
Representative product dimensions	270mm x 110mm x 234mm			
Accessories	No accessories needed			
Date of information release	07-2024			



♠ Additional information

Leg	ıal	inf	orr	nat	ion

The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.

In case of special transportation: transportation method

No special tranportation

Recyclability potential

50%

Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).

Schneider Electric Industries SAS Country Customer Care Center http://www.se.com/contact 35, rue Joseph Monier

CS 30323

F- 92500 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 928 298 512 €

www.se.com

ENVEOLI1609005_V2

Published by Schneider Electric

© 2023 - Schneider Electric - All rights reserved

07-2024

07-2024 ENVEOLI1609005_V2