



Figure similar

RCBO, 6 kA, 1-pole+N, type AC, 30 mA, B char, In: 16 A, Un AC: 230 V, permitted in all countries. Observe national installation regulations!

| Model | |
|--|---|
| product brand name | SENTRON |
| product designation | RCBO |
| design of the product | Instantaneous |
| General technical data | |
| number of poles | 2 |
| number of poles with protection | 1 |
| design of pole | 1P+N |
| tripping characteristic class | B |
| mechanical service life (operating cycles) typical | 10 000 |
| overvoltage category | III |
| degree of pollution | 2 |
| Voltage | |
| type of voltage of the operating voltage | AC |
| insulation voltage (Ui) rated value | 264 V |
| surge voltage resistance rated value | 4 000 V |
| surge current resistance at (8/20) μ s | 1 kA |
| tripping fault current rated value | 30 mA |
| operational current | |
| • at 30 °C rated value | 16 A |
| • at 40 °C rated value | 15.2 A |
| • at 45 °C rated value | 14.88 A |
| • at 50 °C rated value | 14.4 A |
| • at 55 °C rated value | 13.92 A |
| • at 60 °C rated value | 13.6 A |
| • at 65 °C rated value | 12.96 A |
| • at 70 °C rated value | 12.32 A |
| • at AC rated value | 16 A |
| residual current type | AC |
| Supply voltage | |
| supply voltage | |
| • at AC rated value | 230/240 V |
| • for testing equipment minimum | 195 V |
| operating frequency | 50 Hz |
| supply voltage frequency rated value | 50 Hz |
| Protection class | |
| protection class IP | IP20, if the distribution board is installed, with connected conductors |
| Breaking Capacity | |
| short-circuit current breaking capacity (Icn) according to | 6 kA |

| | |
|---|---------------|
| EN 61009-1 rated value | |
| switching capacity current | |
| <ul style="list-style-type: none"> • according to EN 60898 rated value • according to IEC 60947-2 rated value | 6 kA 15 kA |
| rated residual switching capacity (IΔm) according to IEC 61009-1 | 6 kA |
| energy limitation class | 3 |

Dissipation

| | |
|---|-----|
| power loss [W] | |
| <ul style="list-style-type: none"> • maximum | 3 W |

Product details

| | |
|--|------------|
| product feature touch protection | Yes |
| product component neutral conductor switching | Yes |
| product feature | |
| <ul style="list-style-type: none"> • halogen-free • silicon-free | Yes Yes |

Connections

| | |
|---|--|
| connectable conductor cross-section solid | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 35 mm ² |
| connectable conductor cross-section stranded | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 35 mm ² |
| connectable conductor cross-section finely stranded with core end processing | |
| <ul style="list-style-type: none"> • minimum • maximum | 0.75 mm ² 25 mm ² |
| tightening torque with screw-type terminals | |
| <ul style="list-style-type: none"> • minimum • maximum | 2.5 N·m 3 N·m |
| position of power supply cord | Either top or bottom |

Mechanical Design

| | |
|--------------------------------------|-------|
| height | 90 mm |
| width | 36 mm |
| depth | 77 mm |
| installation depth | 70 mm |
| number of modular width units | 2 |
| mounting position | any |
| net weight | 270 g |
| weight with packaging | 274 g |

Environmental conditions

| | |
|--|-------------------|
| influence of the surrounding temperature | Max. 95% humidity |
| ambient temperature during operation | |
| <ul style="list-style-type: none"> • minimum • maximum | -25 °C 55 °C |
| ambient temperature during storage | |
| <ul style="list-style-type: none"> • minimum • maximum | -40 °C 75 °C |
| number of test cycles for environmental testing according to IEC 60068-2-30 | 28 |

Approvals Certificates

General Product Approval



[Confirmation](#)



| | | | |
|--------------------------|-----|-------------------|-------|
| General Product Approval | EMV | Test Certificates | other |
|--------------------------|-----|-------------------|-------|

[Miscellaneous](#)



[Miscellaneous](#)

[Special Test Certificate](#)

[Miscellaneous](#)

| other | Railway | Dangerous goods | Environment | | |
|------------------------------|-------------------------------|--|------------------------------|---------------------------------------|---|
| Confirmation | Miscellaneous | Special Test Certificate | Confirmation | Transport Information | Environmental Confirmations |

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1356-0KK16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1356-0KK16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1356-0KK16

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/5/2024 

