



# Ledinaire Waterproof

## WT060C LED36S/840 PSU L1200

840 neutral white - Power supply unit

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

### Product data

General Information	
Beam angle of light source	120 °
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Luminaire light beam spread	120°
Control interface	-
Connection	Connection unit 2-pole
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	45

EU RoHS compliant	Yes
Service tag	No
Unified glare rating CEN	Not applicable

### Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	3 A
Inrush time	0.101 ms
Power Factor (Min)	0.9

### Controls and Dimming

Dimmable	No
----------	----

### Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate

# Ledinaire Waterproof

Fixation material	Stainless steel
Optical cover/lens finish	Opal
Overall length	1201 mm
Overall width	69 mm
Overall height	59 mm
Color	Gray and white
Dimensions (Height x Width x Depth)	59 x 69 x 1201 mm (2.3 x 2.7 x 47.3 in)

## Approval and Application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	<5
Initial input power	30 W
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	7.5 %
50000 h	

Lumen maintenance at median useful life*	L70
50000 h	

## Application Conditions

Ambient temperature range	-20 to +45 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes


## Product Data

Full product code	871016336009699
Order product name	WT060C LED36S/840 PSU L1200
EAN/UPC - Product	8710163360096
Order code	911401876680
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401876680
Net Weight (Piece)	0.750 kg



## Dimensional drawing

WT060C



TYPE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
L400	69	69	69	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201
L1200	69	69	69	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201
L1800	69	69	69	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201
L2400	69	69	69	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201	1201

## Waterproof WT055C/WT060C

## Ledinaire Waterproof

