



HYPERCOLOR G12 - CERAMIC BURNER

Typology

Discharge lamps.

Features

Product reliability. This is what the entire range of Duralamp discharge lamps has in common.

Used in technical and professional installations where relamping is often difficult, discharge lamps must be lamps you can depend upon.

Notes

The HYPERCOLOR range with ceramic burners: excellent control of colour uniformity, colour rendering and colour stability over time.

93 Vac

Ra >80



12000 h

IP20


G12

-15°C
+35°C

Characteristic data

Power	150 W	Dimmable	No	Input	93 Vac	Base	G12
IP	20	Flux	14000 lm	Tc	3000 K	Ra	>80

Dimensional characteristics



Ø	30 mm
H	105 mm

Lighting and photometric features

Flux	14000 lm
CCT nominal colour temperature	3000 K
Colour rendering index	>80
Lifespan	12000 h
Mercury	11,6 mg

Electrical characteristics

Rated power	150 W
Input voltage	93 Vac
undefined	50 Hz
Dimmable	No
Input current	1.85 A
Operating temperature	-15°C / +35°C
Operating position	360°

Standards and Directives

2009/125/EC, 245/2009, 347/2010, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62035:2016
CEI EN 55015:2020	CEI EN 62035/A1:2020

Logistics data

Barcode single item	8007753356264
Number of pieces multiple pack	12
Barcode multiple pack	8011905771904