

ECS100100



SLOTTED TRUNKING WITH COVER S 4/6/4 DIM.100X100

Trunkings > Panelboards systems > Trunking systems >
Slotted trunkings > Slotted cable trunking system > Grey - type
s - narrow slots 4/6/4




IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
Type of fastening	Bottom perforation	Width	100 mm	Height	100 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	8980 mm ²	With cover	Yes	RAL-number	7030

Technical Characteristics

Separator predisposition SI (2)

Documentation available for download



Certification

Certificato UL A-S
ATL AMF
E331386.pdf



Certification

RINA_ELE288320
CS001_2020.PDF



Certification

Canali asolati tipo S
IMQ_EI617_2020.p
df

Barcode



8054320286578

Cardboard

16 MT

0.26x0.26x2.03 [m]

18.5008 [kg]



8054320280798

Pallet

192 MT

222.0096 [kg]