



COMPATTA UGR

Apparecchio da incasso professionale LED a bassa luminanza.
LED recessed professional lighting fitting, low luminance.



A RICHIESTA | ON REQUEST



5Y WARRANTY
5% FAILURE RATE

60.000 h
LED LIFETIME L90B10

100.000 h
LED LIFETIME L70B50

Relamping	Lumen LED*	Watt LED**	Lumen Out***	Watt	Lumen Watt Out	Configurazione LED LED configuration	Codice Code	K	Alimentazione Power Supply	Schermo Diffuser	Colore Colour
4x14	3315	17,5	2603	18,5	> 141	=====	CCPM19				
4x18	3937	21,5	3092	22,5	> 137	=====	CCPM23	W: 3.000	— : CAE A RICHIESTA ON REQUEST DL: DALI PD: PUSH DIM	— : microprismato microprismatic	01: bianco white
4x18	4665	25,5	3664	27	> 136	=====	CCPM27	N: 4.000			05: grigio silver
4x24	5120	28,5	4021	30	> 134	=====	CCPM30				



TEMPERATURA AMBIENTE MIN E MAX | MIN AND MAX ROOM TEMPERATURE: (-10° +40°)

* Lumen nominali LED max a 25° | Nominal lumen at max 25°

** Potenza dei LED | LED power

*** Flusso totale in uscita dall'apparecchio a temperatura di lavoro (Ta 25° - 4.000 K) | Total lighting fitting flux output at working temperature (Ta 25° - 4.000 K) | (3.000 K -8% - CRI 90 -10%)



Descrizione prodotto | Product description
p. 86



Schema di cablaggio | Connection scheme
p. XXVIII-XXIX



Fotometrie | Photometries
p. 87