

**900473EX****ALARM-EX SIREN AL 230VAC 2D 3G**

Registry	
Net weight	1,226
Min order quantity	1
EAN Code	8014950010745
Gross Weight	1,331
Reference Standards	Standards
EN 60079-0/A11:2013	2011/65/EU (ROHS)
EN 50581:2012	2012/19/EU (WEEE)
EN 60079-0:2012	2014/30/EU (EMC)
EN 60079-15:2010	2014/34/EU (ATEX)
EN 60079-31:2014	2014/35/EU (LVD)
EN 62080:2009	
Marks	
	
Download EX Instructions / EU Conformity	
Download EX Certificate	
Download IECEX Certificate	

Technical data	
Hole type	M20
Sound level at 1 mt.	107/105dB
Frequency	50/60Hz
Protection degree	IP66
Poles	2P+⚡
Acoustic Signal Type	D
Operational working temp	-20 T 40
Rated operating voltage	230V
Manufacturing material	Aluminium alloy (EN 46100)
Rated current	0.3A
Atex	
ATEX application zone	Zona/Zone 2, 21 and 22
Notified body ATEX	
Certificate Number IECEX	IECEX EXA 16.0011
Atex Dust Nominal Current	-
Atex Gas Nominal Current	-
Atex Dust Marking	Ex tb IIIC T65°C Db
Atex Gas Marking	Ex nA IIC T3 Gc
Certificate No. ATEX EU	TÜV IT 13 ATEX 021
GAS Dissipable Power	-
DUST Dissipable Power	-
Min. Amb. Temp.	-20°C
Max. Amb. Temp.	+40°C
Group & Cat. ATEX GAS	II 3G
Group & Cat. ATEX DUST	II 2D
Attachments	
DXF drawing	