



art. 8033 LORD 3/AR

Mod	AR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	45° asymmetric beam matt satin aluminium reflector.
Power supply	220-240V 50/60Hz	Flicker	Low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	45°		

CODING

Art.	+	Mod.	+	°K	+		+	W-tot.	+	Opt.		
8033		AR		3	=3000°K-CRI80	6	=6500°K-CRI80	130	230	GL	=on/off	GV =vetro infrangibile
				4	=4000°K-CRI80	R	=5700°K-CRI90	150	240	GD	=dali	GA =vetro acidato
				5	=5000°K-CRI80	8	=4000°K-CRI70	200	280	GM	=1-10V	G1 =em. 1h

ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.090	Acc.091	Acc.031	

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
130	3	250W JM	22411	16938	130	395	105	455	8,7
150	3	250W JM/SAP	24880	18804	125	395	105	455	8,7
200	4	400W JM/SAP	35331	26703	134	395	105	455	8,7
230	4	400W JM/SAP	39530	29876	130	395	105	455	8,7
240	4	400W JM/SAP	41208	31144	130	395	105	455	8,7
280	4	600W SAP	46686	35271	126	395	105	455	9

The luminous flux and the total power absorbed by the system have a tolerance of $\pm 10\%$ with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

