



art. 6001 STELLA /24

Mod	24	Insulation class	Class II
Material	Steel sheet ring, painted with embossed white anti-yellowing epoxy-polyester powder, including phosphating and degreasing pretreatment	Installation	Round downlight suitable for all false ceiling types
Protection index	IP40	Impact degree	IK07
Ambient temperature (Ta)	-25 / +45 °C	Optics	Anodized aluminium reflector, anti-glare microprismatic polycarbonate diffuser
UGR	less than 19	Power supply	220-240Vac 50/60Hz
Flicker	Flicker free (less than 3%)	Trademarks and certifications	CE / UNI EN 60598-1:2015 - IMQ
Warranty	7 YEARS	Luminous flux maintenance	L90-B10 (50.000h)-L80-B50 (75.000h)
Photobiological safety class	IEC 62471: Exempt group	Beam angle	90°

CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	+	Opt.			
6001		24		03	=3000°K-CRI80	65	=6500°K-CRI80	11	20	40	EL = standard	E1 =em. 1h
				04	=4000°K-CRI80	94	=4000°K-CRI90	13	26	55	LM = dim 1-10V	E3 =em. 3h
				05	=5000°K-CRI80	93	=3000°K-CRI90	18	30	75	LD =dali	D1 =dali+em. 1h

ACCESSORIES

Acc.017

Acc.035

PERFORMANCE

W-tot	°K-CRI	n° Led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
11	4000K-CRI>80	1	1x26W FL-C	1880	1353	123	240	-	90	0,4
13	4000K-CRI>80	1	1x26W FL-C	2260	1627	125	240	-	90	0,4
18	4000K-CRI>80	1	1x26W FL-C	3192	2298	128	240	-	90	0,4
20	4000K-CRI>80	1	2x26W FL-C	3299	2375	119	240	-	90	0,4
26	4000K-CRI>80	1	2x26W FL-C	4395	3164	122	240	-	90	0,4
30	4000K-CRI>80	1	70W JM	4038	2907	97	240	-	90	0,4
40	4000K-CRI>80	1	400W ALO	6389	4600	115	240	-	90	0,4
55	4000K-CRI>80	1	500W ALO	8336	6001	109	240	-	90	0,4
75	4000K-CRI>80	1	150W JM	10648	7666	102	240	-	90	0,4

The luminous flux and the total power absorbed by the system have a tolerance of $\pm 10\%$ with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

