
## **QUADRA HP/QP**

1806QP0432EL









## **SPECIFIC PRODUCT**

Mod	QP					
Color	Matt white					
Installation	Multi-installation BACKLIGHT led panel, suitable for recessed installation in false ceiling with visible structure 15/24 mm or					
	surface mounting installation (dedicated kit needed)					
Application	Indoor					
Materials	Steel sheet body, painted with embossed white anti-yellowing epoxypolyester powder, including phosphating and degreasing					
	pre-treatment					
Insulation class	Class II					
Protection index	IP 20/40					
Impact degree	IK06					
Ambient temperature (Ta)	'-25 / 45 °C					
Optics	Anti-glare microprismatic polycarbonate diffuser					
Beam angle	90°					
UGR	<19					
Power supply	220-240Vac					
Frequency	50/60Hz					
Led modules	Removable (Class: D)					
Standard equipment	- IP20 independent driver that can be remotely installed in the false ceiling.					
Luminous flux maintenance						
	L80-B50 > 100.000 h					
	L90-B10 > 60.000 h					
Wiring	Removable					
Step Mac Adams	3 step					
Photobiological safety class	Risk exempt group					
Trademarks and certifications	CE / UNI EN 60598-1					
Warranty	7 years					

## **PRODUCT FEATURES**

W tot.	mA	°K - CRI	Options	Lumen OUTPUT	Lm/W	A (mm)	B (mm)	C (mm)	D (mm)	Kg
32	_	4000°K - CRI>80	on/off	4158	130	595	595	35	-	2.2



## **RELATED ACCESSORIES**



ACC002 Brackets included. 620x620 mm. Frame for recessed installation in plasterboard ceiling.



ACC003 Brackets included. 320x1220 mm. Frame for recessed installation in plasterboard ceiling.



ACC006 Suspended installation kit, including: 4 steel 1500 mm length cables; wiring rose.



ACC017 Recessed light and motion sensor for DALI fittings.



**ACC018** Surface light and motion sensor for DALI fittings.



ACC035 Remote control for office sensors (optional).



**ACC037** Frame for ceiling installation.



**ACC145** Ø2 mm steel fall arrest safety cable.



**ACC175** Frame for ceiling installation 300x1200 mm.



TEC-MAR S.r.I. Via delle Industrie 1, 26835 Crespiatica (LO) - Italy

TEC-MAR S.r.I. reserves the right, without notice, to modify the characteristics of its products as well as their availability at any time. All products, related technical data, illustrations and information are not binding for TEC-MAR S.r.I. TEC-MAR S.r.I. will not be liable for any illustrative, textual and/or translation errors. All values reported are measurement values. Flow, CCT and power data are within tolerances of +/- 10%.